

LEGEND SERIES KEYPADS

The M-Flex Legend Series Keypads have relegendable keycaps and are designed for severe duty, outdoor mobile applications and built to withstand the harsh temperatures, shock and vibration, moisture and electrical transients that are common to these environments.

12V

24V







IP67



RoHS



FEATURES



Relegendable keycaps. Standard and custom icons.



Tactile Buttons with actuation feedback.



CAN protocol J1939, CANopen, NMEA 2000.



Multi-colored indicator lights. Full color LED indicators.



Vertical or horizontal mount.



On/off, momentary, toggle scroll/ step functions for each key.



Deutsch DT style connectors.



Compatible with Marlin Digital Switchers and IO Controllers.



Optional Bluetooth connectivity.




SPECIFICATIONS

Specifications subject to change without notice. \ Revised 01.24

Supply Voltage	9 – 32VDC.
Max Current	1A @ 12VDC.
CAN Protocol	J1939, CANopen, NMEA 2000.
Baud Rate	250, 500, 1000 kbps.
Switch Backlighting	Dimmable color LED backlighting on switches; intensity controlled via CAN message.
Actuation	Snap dome contacts operate at 340 grams of force.
Connector	Deutsch DT04-4P.
Mounting	(2) #10-32 bolt; 35 in. lbs torque.
Ingress Protection	IP67.
Operating Temperature	-40° to 85°C (-40° to 185°F).
Storage Temperature	-40° to 85°C (-40° to 185°F).
Enclosure	PC PBT alloy plastic resin.

DIMENSIONS





For a detailed specification visit marlintech.com/m-flex

Marlin Technologies, Inc. 101 Industrial Drive \ P.O. Box 123 Horicon, WI 53032-1803 920.485.4463 \ P 920.485.2899 \ F

MARLINTECH.COM

Made in the USA with Imported Materials